



objects and classes

DAY 8



classes are templates.
objects are specific instances of a class.





classes - factories with instructions on how to construct an object when invoked by program.



objects - a specific member of the class; made of variables, functions (methods), constructor.



objects are specific instances of a class.
methods are actions an object can perform.



Plan

- 1. specify the class - methods - variables,
 - 2. call the class to instantiate objects.
-
- But first, group exercise!




Exercise

What are some examples of classes, objects, and methods in everyday (or not so everyday) life?

Classes

Objects (or Instances)

Methods (functions)?



```
StartEngine();
```

```
StopEngine();
```

```
Open(int door);
```

```
Close(int door);
```

```
Turn(int direct);
```

```
etc...
```

Bouncing Ball: object oriented version

```
//Main BouncingBall Program

void setup() {
  size (600,600);
  smooth();
}

void draw () {
  background (0);
}
```


```
//NAME OF CLASS
class BouncingBall {

//VARIABLES

//THE CONSTRUCTOR

//FUNCTIONS
}
```


myBall, an instance of class BouncingBall



```


Main_BouncingBall_Program  BouncingBall_Class
//Declared
BouncingBall myBall; <-- DECLARE A CLASS LIKE A VARIABLE

    In previous lessons, to
    declare variables, we
    prefixed the names of
    our variables with the type.
    Often we used "Int" or "Float"
    and then followed the type
    with a name of our choice.
    Now, to declare OBJECT
    CLASSES, the class type is
    the actual name of the class
    (in this case BouncingBall)
    and then you follow the type
    with a name of our choice.
    I use "myBall" to declare my
    class below.

//Initializes
void setup() {
    size (600,600);
    smooth();
    myBall = new BouncingBall (); <-- The keyword "new" is saying
    build a new instance of the class.
}

//Functionality
void draw () {
    background (0);
    myBall.display(); <--This is a function of the class, the dot syntax
    opens up the class and its functions. In this case
    we have one function, display()
}

```



```

Main_BouncingBall_Program  BouncingBall_Class  Java
class BouncingBall {

    //VARAIBLES (Note: these variables are global to the class, you are just declaring them here)
    float x = 0;
    float y = 0;

    //THE CONSTRUCTOR (Note: the constructor runs only once when called it is not a looping function)
    BouncingBall(){
    }

    //FUNCTIONS
    void display () {
        ellipse (200,200,20,20);
    }
}

```

```
class BouncingBall {

    //GLOBAL VARIABLES (Specific only to the BouncingBall class)
    float x = 0;
    float y = 0;

    //THE CONSTRUCTOR
    BouncingBall(float _x, float _y){ // <-- Here, we are adding the variables _x and _y inside the constructor.
        // _x and _y are only visible to the constructor. We need _x and _y
        // as place holders so we can manipulate our objects in the main program.

        x = _x; // <-- We also want our objects to access the functionality below. To do this
        y = _y; // we set our _x and _y place holders to equal our class's global variables x and y.
    }

    //FUNCTIONS
    void display () {
        ellipse (x,y,20,20); // <-- We replace the first two values in the ellipse with x and y so we can have
        // choices for its functionality.
    }
}
```

```
//Main BouncingBall Program

//Declared
BouncingBall myBall;

//Initializes
void setup() {
    size (600,600);
    smooth();
    myBall = new BouncingBall (400,400); // <-- The constructor has two place marker arguments, _x and _y.
        // So, we must add in two arguments here to match the number of place
        // markers. Here we add in 400,400 to change the position of our ellipse.
}

//Functionality
void draw () {
    background (0);
    myBall.display();
}
```

```
class BouncingBall {

    //GLOBAL VARIABLES (two additions)
    float x = 0;
    float y = 0;
    float speedX = 4;
    float speedY = .5;

    //THE CONSTRUCTOR (no change)
    BouncingBall(float _x, float _y){
        x = _x;
        y = _y;
    }

    //FUNCTIONS (3 more functions added)

    void move() { //move the ball around the screen
        x = x + speedX;
        y = y + speedY;
    }

    void bounce(){ //bounce the ball when you get to the edges.
        if ((x > width) || (x < 0)){
            speedX = speedX * -1;
        }
        if ((y > height) || (y < 0)){
            speedY = speedY * -1;
        }
    }

    void gravity(){ //mimic gravity by changing speed on y axis.
        speedY = speedY + 0.2;
    }

    void display () { //display the ball
        ellipse (x,y,20,20);
    }
}
```

```
Main_BouncingBall_Program BouncingBall_Class
//Main BouncingBall Program

//Declared
BouncingBall myBall;

//Initializes
void setup() {
  size (600,600);
  smooth();
  myBall = new BouncingBall (400,400);
}

//Functionality
void draw () {
  background (0);
  myBall.display();
  myBall.move();
  myBall.bounce();
  myBall.gravity();
}
```

```
Main_BouncingBall_Program BouncingBall_Class
class BouncingBall {

  //GLOBAL VARIABLES
  float x = 0;
  float y = 0;
  float speedX = 4;
  float speedY = .5;

  //THE CONSTRUCTOR
  BouncingBall(float _x, float _y){
    x = _x;
    y = _y;
  }

  //FUNCTIONS


  void run(){ // New comprehensive function called run that lumps them all together in one move.
    move();
    bounce();
    gravity();
    display();
  }

  void move() {
    x = x + speedX;
    y = y + speedY;
  }

  void bounce(){
    if ((x > width) || (x < 0)){
      speedX = speedX * -1;
    }
    if ((y > height) || (y < 0)){
      speedY = speedY * -1;
    }
  }

  void gravity(){
    speedY = speedY + 0.2;
  }

  void display () { //display the ball
    ellipse (x,y,20,20);
  }
}
```

Main_BouncingBall_Program

BouncingBall_Class

```
//Main BouncingBall Program

//Declared
BouncingBall myBall;

//Initializes
void setup() {
  size (600,600);
  smooth();
  myBall = new BouncingBall (400,400);
}

//Functionality
void draw () {
  background (0);
  myBall.run(); //Just one function needed here now, run()
}
```



Main_BouncingBall_Program

BouncingBall_Class

```
//Main BouncingBall Program


//Declared
BouncingBall myBall;
BouncingBall myBall1;
BouncingBall myBall2;
BouncingBall myBall3;
BouncingBall myBall4;

//Initializes
void setup() {
  size (600,600);
  smooth();
  myBall = new BouncingBall (400,400);
  myBall1 = new BouncingBall (30,40);
  myBall2 = new BouncingBall (100,200);
  myBall3 = new BouncingBall (10,400);
  myBall4 = new BouncingBall (300,300);
}

//Functionality
void draw () {
  background (0);
  myBall.run();
  myBall1.run();
  myBall2.run();
  myBall3.run();
  myBall4.run();
}
```

Exercises (for fun)

- Make an array of BouncingBalls and put them at regular spacing around the screen.
- Show the balls' movements (trails) as they are influenced by the physics.



objects and classes

DAY 8